

### House of Switchgear, Control Panel Accessories, Wires & Cables

Pittale Apartment, First Floor, 527 Budhwar Peth, Tapkir Galli,

Pune - 411002. ☎ : 24456774, 24491816, 66029641 / 642.

M : 7875758405 / 08. 7875758265 / 7875758239

Email : sales@sanjayelectricalspune.com • accounts@sanjayelectricalspune.com

[www.sanjayelectricalspune.com](http://www.sanjayelectricalspune.com)

**PRICE LIST**  
WITH EFFECT FROM  
**1-10-2024**



A Digital Multimeters-Palm/Pocket Size					
1	3½ DIGIT / 2000 Count Digital Multimeter with backlight, Audible Continuity, Diode Test, hFE Test, Data Hold & Battery Test functions	MMPL	9030 3100	63+	855
2	3½ DIGIT / 4000 Count Autoranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, REL, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	101B+	1647
3	3 Digt / 6000 Count TRMS Autoranging Pocket Size Digital Multimeter with Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO function	MMPL	9030 3100	108B+TRMS	2115
4	4 Digit / 9999 Count TRMS Autoranging Pocket Size Digital Multimeter with Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Square Wave Output, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	126B+TRMS	2520
5	4 Digit / 9999 Count TRMS Autoranging Pocket Size Digital Multimeter with Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold, NCV and APO functions	MMPL	9030 3100	135B+TRMS	2979
B Digital Multimeters-Professional Type					
1	3½ DIGIT / 2000 Count Digital Multimeter with Holster + Magnet, Backlight, Torch Light, NCV (LED, Buzzer & EF Strength), hFE (Transistor Test), Diode Test, Audible Continuity, Data Hold and APO Functions	MIPL-T	9030 3100	603 JUNIOR	972
2	3 DIGIT / 6000 Count TRMS Autoranging Digital Multimeter with Holster + Magnet, K Type Thermocouple, Temperature, Frequency Capacitance, Duty Cycle, Backlight, Torch Light, APO, NCV (LED, Buzzer & EF Strength), Diode Test, Audible Continuity, Data Hold and APO Functions	MIPL-T	9030 3100	801 JUNIOR	1521
3	3½ DIGIT / 2000 Count Digital Multimeter with 20A AC/DC, hFE, Audible Continuity and Diode Test functions	MMPL	9030 3100	603+	900
4	3½ DIGIT / 2000 Count Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Diode Test, Audible Continuity Data Hold and APO functions	MMPL	9030 3100	9A06	2493
5	3 DIGIT / 6000 Count TRMS Autoranging Digital Multimeter with Holster, Backlight, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	153B+TRMS	2727
6	3½ DIGIT / 4000 Count Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Frequency, Capacitance, Cycle, Diode Test, Audible Continuity, Data Hold and APO function	MMPL	9030 3100	801AUTO	2682
7	3 DIGIT / 6000 Count TRMS Autoranging Digital Multimeter with Holster, K Type Thermocouple, Temperature, Backlight, Frequency Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3100	171B+TRMS	2916
8	3 Digit / 6600 Count Autoranging Digital Multimeter with K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO Functions	MMPL	9030 3100	666TRMS	2736
9	4½ Digit / 19999 Count TRMS Autoranging Digital Multimeter with Backlight, Frequency, Capacitance Duty Cycle, Diode Test, Audible Continuity, Data Hold, NCV, MIN / MAX, ZERO / REL and PO functions	MMPL	9030 3100	450B+TRMS	3753
10	4½ Digit / 20,000 count Digital Multimeter with Holster, Live Wire Check, Infrared Remote Control Check, Capacitance, Frequency hFE Test (Transistor Test), Diode Test, Audible Continuity, Data Hold and APO functions	MIPL-T	9030 3100	45CF	3456
11	3½ Digit / 2000 Count Digital Multimeter with Holster, Automatic Terminal Blocking Mechanism, K Type Thermocouple, Temperature RPM, Ignition Frequency, MS Pulse Width, Backlight, hFE (Transistor Test), Diode Test, Audible Continuity, DataHold and APO functions	MIPL-T	9030 3100	6255	4473
					On Request



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	
C	Digital Clampmeters/tongtesters (AC) - Small				
1	3½ Digit / 2000 Count 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Audible Continuity, Data Hold, Max and APO functions	MIPL-T	9030 3390	2727+	900
2	3½ Digit / 2000 Count 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Audible Continuity, Data Hold, Max and APO functions	MIPL-T	9030 3390	27-T	1368
3	3½ Digit / 2000 Count 600A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple. Temperature, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Audible Continuity, Data Hold, Max and APO functions	MIPL-T	9030 3390	27-AUTO BL	1557
4	3¾ Digit / 4000 Count 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Audible Continuity, Data Hold, capacitance and APO functions	MIPL-T	9030 3390	54+	1431
5	3¾ Digit / 4000 Count 600A AC TRMS Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Frequency, Diode Test, Audible Continuity, Data Hold, REL Test and APO functions	MIPL-T	9030 3390	72-AUTO BL	1773
6	3¾ Digit / 4000 Count 600A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Capacitance, Frequency, Diode Test, Audible Continuity, Data Hold, REL Test and APO functions	MIPL-T	9030 3390	72-T	1971
7	3¾ Digit / 4000 Count 600A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & EF Strenght), Backlight, Torch Light, Diode Test, Data Hold, capacitance and APO functions	MIPL-T	9030 3390	90+	1800
8	3½ Digit / 2000 Count 400A AC Autoranging TRMS Digital Clampmeter with AUTO Sensing of NCV, DCV, Resistance, Audible Continuity and Data Hold functions	MMPL	9030 3390	18 SMART	1557

D	Digital Clampmeters/tongtesters (AC/TRMS)				
				DTT266	774
1	3½ Digit / 2000 Count 1000A AC Manual Ranging Digital Clampmeter with Data Hold, Insulation Test, Resistance and Audible Continuity Functions	MMPL	9030 3390	DTT266(MOQ 10PCS)	7740
2	3½ Digit / 2000 Count 1000A AC Manual Ranging Digital Clampmeter with Data Hold, Insulation Test, Resistance and Audible Continuity Functions	MMPL	9030 3390	DTT266(MOQ 40PCS)	30186
3	3½ Digit / 2000 Count 1000A AC Autoranging Digital Clampmeter with NCV (LED, Buzzer & EF Strenght), Backlight, Tournch Light, K Type Thermocouple, Temperature, Diode Test, Audible Continuty, Data Hold, Max and APO Function	MIPL-T	9030 3390	2502T-AUTO BL	2115
4	3 Digit / 6000 Count 1000A AC Autoranging Digital Clampmeter with K Type Themocouple, Temprature, NCV (LED, Buzzer & EF Strenght), Backlight, Tournch Light, Capacitance, Frequency, Duty Cycle, Diode Test, Audible Continuty, Data Hold and APO Function	MIPL-T	9030 3390	2520THz-AUTO BL	2655
5	3 Digit / 6000 Count 1000A AC TRMS Autoranging Digital Clampmeter with uA Range, Backlight, K Type Themocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuty, Data Hold and APO Function	MMPL	9030 3390	1008-TRMS	4041
6	3¾ Digit / 4200 Count 1000A AC TRMS Autoranging Digital Clampmeter with Frequency, Duty Cycle, Diode Test, Audible Continuty, Data Hold and APO functions	MMPL	9030 3390	2250-Hz AUTO	3006
7	3¾ Digit / 4200 Count 1000A AC TRMS Autoranging Digital Clampmeter with Frequency, Duty Cycle, Diode Test, Audible Continuty, Data Hold and APO functions	MMPL	9030 3390	3150+	2196



SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE
<b>E</b>	<b>Digital Clampmeters/Tongtesters (DC/AC) - Small</b>				
1	3½ Digit / 6000 Count 600A DC/ AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & Strenght), Backlight, Torch Light, Capacitance, Frequency, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO function	MIPL-T	9030 3390	36-AUTO BL	3744
2	3½ Digit / 6000 Count 600A DC/ AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature, NCV (LED, Buzzer & Strenght), Backlight, Torch Light, Capacitance, Diode Test, Audible Continuity, Data Hold Hz / Duty, LoZ (DCV / AC V), VFC and APO function	MIPL-T	9030 3390	99+	3564
3	3¾ Digit / 4000 Count 600A DC/AC TRMS Autoranging Digital Clampmeter with Frequency,Duty Cycle, Diode Test, Audible Continuity, Data Hold, REL and APO functions	MMPL	9030 3390	3690 AUTO	4833

F	Digital Clampmeters/Tongtesters (DC / AC / TRMS)				
1	3¾ Digit / 4200 Count 1200A AC TRMS Autoranging Digital Clampmeter with K Type Thermocouple, Temperature Capacitance, Frequency, Duty Cycle, Max/min, Rel, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	3600BL+	4158
2	3¾ Digit / 6000 Count 1200A DC/AC TERMS Autoranging Digital Clampmeter with uA Range, Backlight, K Type Thermocouple, Temperature, Frequency, Capacitance, Duty Cycle, Diode Test, Audible Continuity, Data Hold and APO function	MMPL	9030 3390	1080-TRMS	5373
3	3¾ Digit / 6000 Count 2000A DC/ 2000A AC TERMS Autoranging Clampmeter with 60 Segment Bargraph with Frequency, Capacitance, Duty Cycle, RPM, MIN-MAX, REL, Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	2003A+	7632
4	3½ Digit 1999 Count 2000 V & A DC / AC TRMS Auto & Manual Ranging Digital Clampmeter with Backlight, Torch Light, Inrush Current, Capacitance Diode Test, Audible Continuity, Data Hold and APO functions	MMPL	9030 3390	4455	8082

SR	DESCRIPTION	ORDER TO	HSN CODE	MODEL	LIST PRICE
<b>G</b>	<b>Analog Insulation Testers</b>				
1	500V-100MW Analog Insulation Tester	MIPL	9030 3390	MC 903	2034
2	500V-500MW Analog Insulation Tester	MIPL	9030 3390	MC 904	2034
3	1000V-200MW Analog Insulation Tester	MIPL	9030 3390	MC 906	2034
4	1000V-500MW Analog Insulation Tester	MIPL	9030 3390	MC 907	2034
5	500V-1000MW Analog Insulation Tester	MIPL	9030 3390	MC 941	2259
6	1000V-2000MW Analog Insulation Tester	MIPL	9030 3390	MC 981	2259

H	Digital Insulation Testers				
1	500V-200MW Digital Insulation Tester	MIPL	9030 3390	DIT99BL - C	1926
2	1000V-200MW Digital Insulation Tester	MIPL	9030 3390	DIT99BL - D	1926
3	1000V-2000MW Digital Insulation Tester	MIPL	9030 3390	DIT99BL - E	1926
4	2.5kV-20GW Digital Insulation Tester with AC Voltage function	MIPL-T	9030 3390	DIT918	7254
5	5kV-200GW Digital Insulation Tester with AC Voltage Phase Sequence and Phase Status Indicator functions	MIPL-T	9030 3390	DIT954	13248
6	5kV-200GW Digital Insulation Tester with Rechargeable Batteries, AC Voltage PhaseSequence and Phase Status Indicator functions	MIPL-T	9030 3390	DIT954-6R	11853



I Clamp - On Earth / Ground Resistance & Leakage Current Testers					
1	Leakage Current Tester with 10mA AC Ultra High Resolution, AC Current (40mA, 400mA, 4A, 40A, 60A), AC Voltage & Resistance Functions, Jaw Opening : For Cable of 30mm Diameter	MMPL	9030 3390	4671	26856
2	Low AC Current Tester upto 10mA AC Resolution, with Large Conductor Diameter (30mm), AC Current (20mA, 200mA, 2A, 60A), ACA, ACV, DCV, Large 3½ Digit LCD (1999), Data Hold, Low Battery Indication and APO functions	MIPL-T	9030 3390	4671A	8658
3	Clamp - On Earth / Ground Resistance Tester (Non Contact Type) with Range : 0.010W - 1000W, Data Storage Memory, Data Hold, Autoranging, Auto Power OI functions, Jaw Opening : for Earthing Strip of 65 x 32mm	MIPL-T	9030 3390	4680BL	34929
4	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.010W - 1000W, 0.5mA - 30.00mA AC, Data Storage Memory, Data Hold, Autoranging, Auto Power OI functions, Jaw Opening : for Earthing Strip of 65 x 32 mm	MIPL-T	9030 3390	4680BLC	39402
5	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.025W - 1500W, 0.300mA - 30.00mA AC, Data Logging, Data Hold, Programmable HI - LO Alarm, Autoranging, Auto Power Off functions, Jaw Opening : for Earthing Wire of 23mm Diameter	MMPL	9030 3390	4680	119700
6	Clamp - On Earth / Ground Resistance and Leakage Current Tester (Non Contact Type) with Range : 0.025W - 1500W, 0.300mA - 35.00mA AC, Data Logging, Data Hold, Programmable HI - LO Alarm, Autoranging, Auto Power Off functions, Jaw Opening : For Earthing Wire of 34.5mm Diameter	MMPL	9030 3390	4680B	134703

J Battery Capacity Testers / Battery Meters					
1	Automotive Battery Meter : 2200Ah, 2-6-12V DC, with Internal Resistive Load Indicates Battery Condition as FULL / NORMAL RECHARGE / DISCHARGE	MMPL	9030 3390	ABM18	1494
2	Battery Meter : 4-500Ah, 2-6-12V DC, with DC Voltmeter upto 0 - 15 VDC and Internal Resistive Load, Indicates Battery Condition as OK/ WEAK/BAD	MIPL-T	9030 3390	BM63	2097
3	Digital Battery Meter : 40 - 200 Ah, 6/12V DC with Internal DC Voltmeter upto 0 - 19.99V DC and Internal Resistive Load with Built-In Timer and Charging Test, Indicates Battery Condition as GOOD/WEAK / BAD and Auto Data Hold function	MIPL-T	9030 3390	DBM72	6939
4	Battery Capacity (Impedence) Tester : Upto 500 Ah & 40V DO with PC Communication, with Software, Comparator Function, Measures Online Internal Impedence / Resistance and Open Circuit Voltage for All Types of Batteries	MMPL	9030 3390	6363	88308

K Environment Testing Instrument					
1	Humidity & Temperature Meter : 0 to 100% RH, - 20 to 80°C, °C/°F /RH Selection, MAX/MIN, Auto Power OI	MMPL	9030 3390	920P	3195
2	Digital LUX Meter (with Flexible Cord Sensor) : 0 - 2,00,000 lux / 0 -20,000 fc, MAX/MIN, Backlight, Auto Power OI with Disable Function, Data Hold	MMPL	9027 8090	930T	2817
3	Digital LUX Meter : 0-2,00,000 lux / 0 - 20,000 fc, MAX / MIN, Backlight, Auto Power OI	MMPL	9027 8090	930P	2817
4	Air Flow Anemometer : 1 - 25m/s, 0 to +50°C, m/Sec, Ft / min, Knots, Km / h, MPH, CFM, MAX / MIN / HOLD, Auto Power OI	MMPL	9030 3390	961P	2520
5	Digital Sound Level Meter : 35dB - 130dB (31.5 Frequency to 8K Frequency), MAX / MIN / HOLD, Auto Power OI	MMPL	9027 8090	970P	2403
6	Infrared Thermometer : 50°C to 600°C/-58°F to 1112°F, °C / °F Selection, Backlight, MAX /MIN, APO functions	MIPL	9025 1990	IRT600T	1251
7	Infrared Thermometer : 50°C to 1050°C/-58°F to 1922 °F, °C/°F Selection, Backlight, MAX / MIN / DIF / AVG / Data Storage, Auto Power OI	MMPL	9025 1990	IRT 1050P	9486
8	Laser Distance Meter : 0.05 to 60m, Units : m/in/ft/ft'in", Functions :Addition, Subtraction, Area, Volume Pythagorean, Data Storage	MMPL	9027 8090	LDM60+	3816
9	Laser Distance Meter : 0.05 to 100m, Units : m/in/ft/ft'in", Functions :Addition, Subtraction, Area, Volume Pythagorean, Data Storage, Backlight, MIN / MAX, Timer Selection, Historical Storage	MMPL	9025 8090	LDM100+	4473



L Clamp-On Power Meters					
1	Clamp-On TRMS Power Meter (1000A, 600kW) Autoranging with Dual Display, Automatic Computation of 1 Phase and 3 Phase (3P3W/3P4W) Parameters. Measures : TRMS AC A, AC / DC V, TRUE Power, HP, KW, KVA, KVAR, HZ, PF, AC Inrush Current, TRMS uA (AC + DC) Phase Angle, 3 Phase Sequence Indicator Resistance (Continuity), Capacitance, Diode, Temperature, Data Hold and Auto Power Off. Jaw Opening : For Cable / Conductor upto 43mm/ Busbar upto 98mm x 16mm	MIPL-T	9030 3390	3510PHW AUTO	12744
2	3Phase / 1Phase TRMS Clamp On Autoranging Power Meter for AC/DC Power Measurement (2000A, 2000kW) with PF, Phase Angle, Frequency & Memory for Recording. Jaw Opening : For Cable of 55mm Diameter / Bus Bar 65 x 24mm	MMPL	9030 3390	4500	47124

M POWERGUARD					
1	POWERGUARD having Indian Plug - Socket and Backlight to Display : W (0.2 - 2200.0W), PF, CO2 (kg), TUT, Money, Tarrif, Frequency, KWh, V (1995.00 - 265.00V AC) and mA (10000mA max.), Built - In Programmable ON / OFF Relay with Timer Function for Control of Load	MIPL-T	9030 3390	PG08T	1575
2	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : KW (0.024 - 1.440KW), V (195.0 - 265.0V AC), Frequency, A (0.100 - 6.000A) PF, KVA, KVAR, KWh, EUT and CO2 (kg)	MIPL	9030 3390	PG09 - 5A	2250 on Request
3	POWERGUARD having Indian Plug - Socket and Backlight to Display TRMS : KW (0.026 - 4.800KW), V (195.0 - 265.0V AC), Frequency, A (0.110 - 20.00A) PF, KVAR, KWh, EUT and CO2 (kg)	MIPL	9030 3390	PG09 - 20A	2430

SR	DESCRIPTION	MODEL	LIST PRICE
----	-------------	-------	------------

N Phase Sequence Indicator					
1	Phase Sequence Indicator of Voltage Range : 60-600V AC, Frequency Range : 40 - 400Hz with LED Indication and Buzzer	MIPL	9030 3390	PSI2016	1449
2	Inverter Analyzer	MIPL	9030 3390	IA-S	666

**SANJAY**  
electrical

**House of Switchgear, Control Panel  
Accessories, Wires & Cables**

Pittale Apartment, First Floor, 527 Budhwar Peth,  
Tapkir Galli, Pune - 411002.  
☎ : 24456774, 24491816, 66029641 / 642.  
M : 7875758405 / 08. 7875758265 / 7875758239  
Email : sales@sanjayelectricalspune.com  
● accounts@sanjayelectricalspune.com  
www.sanjayelectricalspune.com

**TERMS & CONDITIONS :**

- PRICES ARE SUBJECT TO CHANGE WITHOUT ANY PRIOR NOTICE.
- GST EXTRA AS APPLICABLE
- GOODS SOLD WILL NOT BE TAKEN BACK
- THIS PRICE LIST CANCELS ALL OUR PREVIOUS PRICE LISTS.
- SUBJECT TO PUNE JURISDICTION ONLY.

### House of Switchgear, Control Panel Accessories, Wires & Cables

Pittale Apartment, First Floor, 527 Budhwar Peth, Tapkir Galli,  
Pune - 411002. ☎ : 24456774, 24491816, 66029641 / 642.

M : 7875758405 / 08. 7875758265 / 7875758239

Email : sales@sanjayelectricalspune.com • accounts@sanjayelectricalspune.com

[www.sanjayelectricalspune.com](http://www.sanjayelectricalspune.com)



**PRICE LIST**  
WITH EFFECT FROM  
**1-10-2024**

A	3 Phase VAF / VIF Meter - TRMS (HSN 90303390)		Unit Rate
Sr	Mode		
1	VIF96U		1260

B	3 Phase Multifunction Power & Energy Monitor/ Power Line Supervisor TRMS (HSN:90303390)	RS-485 Port, 5 KV Isolated, MODBUS RTU Protocol & POWER MASTER Software	Unit Rate
Sr	Mode		
1	MFM-96S	-	3663

C	1 Phase Multifunction Meter TRMS [HSN: 90303390]	RS - 485 Port, 5 KV Isolated, MODBUS RTD Protocol & POWER MASTER Software	Unit Rate
Sr.	Model		
1	EM08 (1A or 5A)	-	2544
2	EM08 (20A Direct)	-	2870

D	1 Phase Multifunction Appliance Meter - TRMS [HSN : 90303390]	RS - 485 Port, 5 KV Isolated, MODBUS RTD Protocol & POWER MASTER Software	Unit Rate
Sr.	Model		
1	EM09 (1A or 5A) (Portable)	-	2640
2	EM09 (1A or 5A) (Portable) - RS 485	-	3300
3	EM09 (20A) (Portable)		2970
4	EM09 (20A) (Portable) RS 485		3520

**Note :** Works Calibration Certificate Traceable to NOL ( ) 250 extra

**C) 4 Digit 3 Phase Programmable Ammeters and Voltmeters (48x96mm, 96x96mm) [HSN : 90303310]**

Model	Input	Range	Programmable Display / CTP / PTR	Auxiliary Power Supply SMPS - HV 85-265V AC/DC
SMP35VSN SMP35ASN (48X96MM)	V	50-500V AC	0-9999	1053
	A	For 1A Range : 0.080-1.200A AC For 5A Range : 0.200-6.000A AC		
SMP9635VSN SMP9635ASN (96X96MM)	V	50 - 500V AC		
	A	For 1A Range : 0.080-1.200A AC For 5A Range : 0.200-6.000A AC		

**Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.

2. SMPS-LV (19-90V AC/DC) on request.



**A) 4 Digit Programmable Ammeter, 3 & 4 Digit Programmable Voltmeter - TRMS**  
(72x72mm, 48x96mm and 96x96mm) [HSN : 90303310]

Model	Input	Range (any one Only)	Programmable Display Key	Digits (Max.)		Auxiliary Power Supply (any one only)		
				3	4	24/48V DC	SMPS-LV 19-90V AC/DC	SMPS-HV 85-265V AC/DC (Standard)
SMP72 (72x72mm)/ SMP48 (48x96mm)/ SMP96 (96x96mm)	DC	mV (Shunt Operated)						
		0 - 50						
		0 - 60						
		0 - 75						
		0-100						
		0-150						
	AC	V	0-2, 20, 200, 1000					
		mV	0 - 2, 20, 200					
		A	0 - 2, 5, 20 (Direct)					
		V	0-20, 200					
AC	V	750						
		750						
	A	110 (PT Operated)						
		0-1, 5 (CT Operated)						
		0-20 (Direct)						

**Note :** 1. Works Calibration Certificate Traceable to NPL ( ) 50 extra.  
2. Factory Test Certificate ( ) 25 Extra

**D) 3½ Digit Ammeters and Voltmeters (48x96mm) [HSN : 90303310]**

Model	Input	Range (any one Only)	Auxiliary Power Supply (any one only)			
			24/48V DC	SMPS-LV 19-90V AC/DC	SMPS-HV 85-265V AC/DC (Standard)	
SMP35SW TRMS (48 x 96mm)	DC	mV	0-50, 60, 75, 200	857	920	794
		V	0-2, 20, 200, 1000			
		mV	0 - 2, 20, 200			
		A	1 - 1, 2, 5, 20			
		Zero Supp.	4 - 20mA or 1 - 5V	970	1053	907
	AC	V	0 - 2, 20, 200, 750	912	998	849
A		0 - 1, 2, 20				
SMP35SRS	DC	#Re- Scaleable	4 - 20mA or 1 - 5V	970	1053	907
		#Re- Scaleable	0*50 / 0 - 60 / 0 -75mV / 0-5V / 0 - 10V / 0 - 20mA			
	AC	#Re- Scaleable	0 - 1A/ 0 - 5A	912	998	849

**Note :** 1. Non Standard Calibration like RPM, Degree Centigrade, M/Min etc at ( ) 40 extra.  
2. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.  
3. AC Meters Calibrated for 400 Hz at ( ) 50 extra  
4. # This meter display is Re-Scalable from 0.100 to 1600 in 64 steps.



E) 3½ Digit Ammeters and Voltmeters (96x96mm) [HSN : 90303310]							
Model	Input		Range (any one Only)	Auxiliary Power Supply (any one only)			
				24/48V DC	SMPS-LV 19-90V AC/DC	SMPS-HV 85-265V AC/DC (Standard)	
SMP9635SW TRMS (96X96mm)	DC	mV	0 - 50, 60, 75, 200	970	1033	907	
		V	0 - 2, 20, 200, 1000				
		mV	0 - 2, 20, 200				
		A	0 - 1. 2. 5. 20				
	Zero Supp	4 - 20mA or 1 - 5V		1086	1149	1023	
	AC	V	0 - 2, 20, 200, 750		1028	1091	965
A		0 - 1, 2, 5, 20					
SMP9635SRS	DC	#Re-	4 - 20mA or 1 - 5V		1086	1149	1023
		Scaleable	0-50/0-60/0-75mV/0-5V		970	1033	907
		#Re-	0-10V/0-20mA				
	AC	Scaleable	0-1A/0-5A		1025	1091	965

- Note :**
1. Non Standard Calibration like RPM, Degree Centigrade, M/Min etc at ( ) 40 extra.
  2. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.
  3. AC Meters Calibrated for 400 Hz at ( ) 50 extra
  4. # This meter display is Re-Scalable from 0.100 to 1600 in 64 steps.

E) 3Digit mA Meter for Power Factor Indication (48x96mm, 96x96mm) [HSN : 90303310]					
Model	Input		Range	Auxiliary Power Supply (any one only)	
				SMPS-LV 19-90V AC/DC	SMPS-HV 85-265V AC/DC (Standard)
SMP35S (48x96mm) SMP9635S (96X96mm)	DC	mA	4 / 12 / 20mA for 0.500 Lag / 1.000 / 0.500 Lead	1226	1100
				1336	1210

- Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.

G) 2 Digit Transformer Tap Position Indication (48x96mm, 96x96mm) [HSN : 90303310]					
Model	Input		Range	Auxiliary Power Supply (any one only)	
				110/ 230V AC	24/48/110/ 220V DC
SMPTCS (48X96mm) SMP96TCS (96X96mm)	DC	TAP POSITION	4 - 20mA DC from Transducer to Display "01 for 4mA DC" and "02 to 99 for 20mA DC".	1438	1501
				1548	1611

- Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.





H) 3 Phase Digital Ammeters and Voltmeters with Built-In Selector Switch (96x96mm) [HSN : 90303310]				
Model	Input		Range	Auxiliary Power Supply (any one only)
				230V AC (Standard) 110V AC (Optional)
SMP9635AS (96X96mm)	AC	A - 3 Phase	1 or 5 (any one only)	990
SMP9635VS33 (96X96mm)		V - 3 Phase 2 Element 3 Wire	63.5, 110, 230, 440 or 750 (any one only)	
SMP9635VS34 (96X96mm)		V - 3 Phase 3 Element 4 Wire		

**Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.

J) 4½ Digit Ammeters and Voltmeters (48x96mm, 96x96mm) [HSN : 90303310]						
Model	Input		Range (any one Only)	Auxiliary Power Supply (any one only)		
				SMPS-HV 85-265V AC/DC (Standard)	24/48V DC	SMPS-LV 19-90V AC/DC
SMP45S / (#)SMP45SW -TRMS (48X96mm)	DC	mV	0 - 200	1048	1111	1174
		V	0 - 2, 20, 200, 1000			
		mV	0 - 2, 20, 20			
		A	0 - 1, 2, 5			
		Zero Supp.	4 - 20mA or 1 - 5V			
	AC	V	0 - 2, 20, 200, 750	1103	1166	1229
SMP9645S / (#)SMP9645SW -TRMS (96X96mm)	DC	mV	0 - 200	1158	1221	1284
		V	0 - 2, 20, 200, 1000			
		mV	0 - 2, 20, 200			
		A	0 - 1, 2, 5			
		Zero Supp.	4 - 20mA or 1-5V			
	AC	V	0 - 2, 20, 200, 750	1218	1281	1344
	A	0 - 1, 2, 5				

- Note :**
1. Non Standard Calibration like RPM, Degree Centigrade, M/Min etc at ( ) 40 extra.
  2. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.
  3. AC Meters Calibrated for 400 Hz at ( ) 50 extra
  4. # RS485 Communication for SMP45SW-TRMS and SMP9645SW-TRMS ( ) 750 extra.



**Q)4 Digit Frequency Meters & RPM Meters (48x96mm, 96x96mm, 72x144mm, 144x144mm) [HSN : 90303340]**

Model	Input		Auxiliary Power Supply (any one only)	
			Self Powered/110/230V AC	24/48/110/220V DC
FDM4S (48X96mm)	40 - 99.99 Hz/ 40 - 5000Hz (Auto Ranging)	20 - 500V AC For 110V AC or 230V AC Aux. Meters For (#) Self Powered Meters Input Variation is $\pm$ 20% of Aux.	600	-
FDM964S (96X96mm)			625	-
FDM1444SA (144X144mm)	40 - 99.99Hz		1713	-
FDM1444SB (144X144mm)			-	2263
FDM72X1444SA (72X144mm)			1713	-
FDM72X1444SB (72X144mm)			-	2263
RPM3AS (48X96mm)	300 - 1500RPM for 10 - 50Hz		600	-
RPM963AS (96X96mm)			625	-

- Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 150 extra.  
2. For Self Powered Input Variation is  $\pm$  20% of Input.

**R)4 Digit Double Frequency Meters (96x96mm, 144x144mm) [HSN : 90303340]**

Model	Input 1 Input 2		Auxiliary Power Supply (any one only)	
			Self Powered/110/230V AC	24/48/110/220V DC
FDM1444D (144X144mm)	40 - 99.99 Hz	Input 20 - 500V AC for 110V AC or 230V AC or DC Aux. and for Self Powered Input Variation is $\pm$ 20% of Aux.	3426	-
FDM1444BD (144X144mm)			-	4652
FDM964SD (96X96mm)	40 - 99.99Hz/ 40 -5000Hz		1250	-

- Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 200 extra.

**S) 5 Digit 3 Phase Watt / VAR / VA Meter (with Built-in Transducer) - TRMS with RS 485 PORT (Optional) (72x144mm) [HSN : 90303310]**

**4 Digit 3 Phase Power Factor Meter (with Built-in Transducer) - TRMS with RS 485 PORT (Optional) (72x144mm) [HSN : 90303310]**

Model	Input (Phase, Element, Wire) (any one only)		Auxiliary Power Supply	
			SMPS-HV 85-265V AC/DC (Standard)	SMPS-LV 19-90V AC/DC
DWM 72X144533 - TRMS DVM 72X144533 - TRMS DVAM 72X144533 - TRMS	3P 2W 3Q	<b>0.1A to 1.2A (Max.) 0.5A to 6A (Max) 190V - 290V AC (Max.) (PH - N) 50.8V - 96.2V AC (Max.) (PH - N) 330V - 500V AC (Max.) (PH - PH) 88V - 132V AC (Max.) (PH - PH)</b>	3772	4098
DWM 72X144534 - TRMS DVM 72X144534 - TRMS DVAM 72X144534 - TRMS	3P 3E 4W		3992	4318
DPF 72X14433 - TRMS	3P 2E 3W		3473	3600
DPF 72X14434 - TRMS	3P 3E 4W			

- Note :** 1. Our Works Calibration Certificate Traceable to NPL at ( ) 250 extra.  
2. Rs 485 Communication at ( ) 500 extra.



**T) Digital Power Factor Meters (with Built-in Transducer) (48x96mm, 96x96mm, 72x144mm, 144x144mm) [HSN : 90303340]**

Model	System (Phase, Element, Wire)	Input (any one only)	Auxiliary Power Supply (any one only)		
			110/230V AC	24/48/110/220V DC	Self Powered
DPF11 (48X96mm)	1P 1E 2W	1A / 5A, 110 / 230V	-	-	2673
DPF31 (48X96mm)	3P 1E 2W (Balanced Load)	1A / 5A, 110 / 440V			
DPF9611S (96X96mm)	1P 1E 2W	1A / 5A, 110 / 230V	2899	3324	2899
DPF9631S (96X96mm)	3P 1E 2W (Balanced Load)	1A / 5A, 110 / 440V			
DPF9634S-TRMS (96X96mm)	3P 3E 4W (BALANCED & UNBALANCED IOAD)	1A / 5A, 110 / 440V	3069	-	-
DPF14411 (144X144mm)	1P 1E 2W	1A / 5A, 110 / 230V	3273	3698	3273
DPF14431 (144X144mm)	3P 1E 2W (Balanced Load)	1A / 5A, 110 / 440V			
DPF72X14411 (72X144mm)	1P 1E 2W	1A / 5A, 110 / 230V			
DPF72X14431 (72X144mm)	3P 1E 2W (Balanced Load)	1A / 5A, 110 / 440V			

**Note : 1.** Our Works Calibration Certificate Traceable to NPL at ( ) 250 extra.

**U) 3½ & 4½ Digit Wattmeters / Varmeters (with Built-in Transducer) (96x96mm) [HSN : 90303310]**

Model	Digit (Max)		Input (Phase, Element, Wire) (any one only)	Auxiliary Power Supply (any one only)	
	3½	4½		110/230V AC	Self Powered
DWM963511 DVM963511		-	1P 1E 2W	1A / 5A, 110 / 440V	2338
DWM964511 DVM964511	-				2933
DWM963531 DVM963531		-	3P 1E 2W (Balanced Load)		2338
DWM964531 DVM964531	-				2933
DWM963533 DVM963533		-	3P 2E 3W (Balanced & Unbalanced Load)		3039
DWM964533 DVM964533	-				3634
DWM963534 DVM963534		-	3P 3E 4W (Balanced & Unbalanced Load)		3086(Note 2)
DWM964534 DVM964534	-				3681(Note 2)

**Note : 1.** Our Works Calibration Certificate Traceable to NPL at ( ) 250 extra.

**2.** Model : DWM963534, DVM963534, DWM964534, DVM964534 available with Self Powered Auxiliary Supply Only.

AC	DIN	SQ HSN
Sr	Ranges	SQ 72    SQ 96
1	0 - 1A to 0 - 30A (Direct)	359    390
2	0 - 40A to 0 - 100A (Direct)	452    470
3	0 - 50V to 0 - 300V	341    452
4	0 - 500V	391    470
5	0 - 750V	468    650

**B** DC Moving Coil 90 DIN Panel Ammeters & Voltmeters (Fixed Scale Type) - M H : 90303310]  
**A** AC Moving Coil 90Rectifier Type DIN Panel Ammeters & Voltmeters (Fixed Scale Type) C H : 903033101  
 Moving iron 90Panel Ammeters & Voltmeters (Interchangeable /Sliding Scale Type) 9030331

Sr	Type	Ranges	M72	M96	C72	C96
1	Micro Ammeter	0 - 100microA to 0 - 750microA	681	737	-	-
2	Milli Ammeter	0 - 1mA to 0 - 60mA	576	632	681	749
3	Ammeter	0 - 75mA to 0 - 750mA			848**	817
4		0 - 1A to 0 - 50A (Direct)			786	819**
5		0 - 5A/75mV to 0 - 6000A/75mV				
6	Milli Voltmeter	0 - 50mVto 0 - 750mV			681	718
7	Voltmeter	0 - 1V to 0 - 6V				
8		0 - 10V to 0 - 60V				
9		0 - 75V to 0 - 1000V	619			

**H** Electronic Analog Type Watt, Var, Power Factor & Frequency Meters [HSN: 90303310]

Type	A	V	90° Deflection			240° Deflection			
			72x72	96x96	144x144	72x72	96x96	144x144	110x110

Sr	ACWatt Meters									
1	1P 1E 2W	1A, 5A, 10A	63.5c or 230V	*72QW11 1229	96QW11 1229	144QW11 1595	*72LW11 2664	96LW11 2664	144LW11 2835	*110LW11 4761
2	3P 1E 2W ** (Balanced Load Star Connection)	1A, 5A, 10A	110V or 440V	*72QWB1 1229	96QW31 1229	144QW31 1595	*72LW31 2664	96LW31 2664	144LW31 2835	*110LW31 4761
3	3P 2E 3W ** (Balanced & Unbalanced Load)	1A, or, 5A	110V or 440V	*72QWB2 2540	96QW32 2540	144QW32 2895	*72LW32 3780	96LW32 3780	144LW32 4016	*110LW32 5883
4	3P 3E 4W (Balanced & Unbalanced Load)	1A, or, 5A	110V/3 or 440V/3	*72QWB3 3131	96QW33 3131	144QW33 3544	*72LW33 3963	96LW33 3963	144LW33 4105	*110LW33 6237

**Power Factor Meters/Phase Angle Meters [HSN Code : 90303390]**

9	1P 1E 2W	1A, or, 5A	63.5V, 230V	#72QF11 1494	96QF11 1494	144QF11 1712	#72LF11 3756	96LF11 3756	144LF11 3460	110LF11 3833
10	3P 1E 2W (Balanced Load)	1A, or, 5A	110V, 440V	#72QF31 1494	96QF31 1494	144QF31 1712	#72LF31 3756	96LF31 3756	144LF31 3460	110LF11 3833

**Frequency Meters [HSN Code : 90303340]**

11	40-60Hz, 45-55Hz, 45-65Hz, 360-440Hz	63.5V 110V 230V 440V	F72 691	F96 821	F144 1819	#FL72 1712	FL96 1518	FL144 1677	FI110 1601
----	--------------------------------------	----------------------	---------	---------	-----------	------------	-----------	------------	------------

**SANJAY**  
electrical

**House of Switchgear, Control Panel Accessories, Wires & Cables**  
 Pittale Apartment, First Floor, 527 Budhwar Peth, Tapkir Galli, Pune - 411002.  
 ☎ : 24456774, 24491816, 66029641 / 642.  
 M : 7875758405 / 08. 7875758265 / 7875758239  
 Email : sales@sanjayelectricalspune.com  
 ● accounts@sanjayelectricalspune.com  
 www.sanjayelectricalspune.com

**TERMS & CONDITIONS :**

- PRICES ARE SUBJECT TO CHANGE WITHOUT ANY PRIOR NOTICE.
- GST EXTRA AS APPLICABLE
- GOODS SOLD WILL NOT BE TAKEN BACK
- THIS PRICE LIST CANCELS ALL OUR PREVIOUS PRICE LISTS.
- SUBJECT TO PUNE JURISDICTION ONLY.

**House of Switchgear, Control Panel Accessories, Wires & Cables**

 Pittale Apartment, First Floor, 527 Budhwar Peth, Tapkir Galli,  
Pune - 411002. ☎ : 24456774, 24491816, 66029641 / 642.

M : 7875758405 / 08. 7875758265 / 7875758239

Email : sales@sanjayelectricalspune.com • accounts@sanjayelectricalspune.com

[www.sanjayelectricalspune.com](http://www.sanjayelectricalspune.com)
**PRICE LIST**  
WITH EFFECT FROM  
**1-10-2024**


AN ISO 9001:2015 COMPANY

	MODEL	DESCRIPTION	COMPANY REFERENCE	HSN CODE	UNIT PRICE
	<b>BASIC DIGITAL MULTIMETERS</b>				
	801-L	3 <sup>3</sup> / <sub>4</sub> Digit 3999 Counts Large LCD Display Digital Mul meter	Kusam LLP	90303100	2,675.00
	702	3 <sup>1</sup> / <sub>2</sub> Digit 2000 Counts Liquid Crystal LCD Display DMM	Kusam LLP	90303100	1,175.00
	603	3 <sup>1</sup> / <sub>2</sub> Digit 1999 Counts Large LCD Display Digital Multimeter	Kusam LLP	90303100	1,850.00
	207-MK-1(T)	3 <sup>3</sup> / <sub>4</sub> Digit 4000 Counts Autoranging Digital Multimeter	Kusam LLP	90303100	2,475.00
	108	3 <sup>1</sup> / <sub>2</sub> Digit 1999 Counts LCD Display Digital Mul er with 10A fused.	Kusam LLP	90303100	1,325.00
	<b>DIGITAL LCR + MULTIMETERS &amp; CAPACITANCE METER</b>				
	333	3 1/2 Digit 1999 Counts Capacitance Meter with Capacitor Discharge Func on	Kusam LLP	90303390	3,350.00
	307	3 3/4 Digit 4000 Counts Autoranging DMM + LCR Meter	Kusam Ele	90303390	6,350.00
	<b>UL/ETL 'APPROVED DIGITAL CLAMP METER</b>				
	2799	3 <sup>3</sup> / <sub>4</sub> Digit 4000 Counts (600A) Dual Display Autoranging Digital Clampmeter for HAVC Applica n (Separate Display for Voltage and Current)	Kusam LLP	90303100	9,975.00
	2754A	3 <sup>3</sup> / <sub>4</sub> Digit 4000 Counts AC/DC Aurtoranging Digital Clampmeter with Multimeter Ranges (1000A DC/800A AC)	Kusam LLP	90303100	9,575.00
	2754A(T)	3 <sup>3</sup> / <sub>4</sub> Digit 4000 Counts AC/DC TRMS Aurtoranging Digital Clampmeter with Multimeter Ranges (1000A DC/800A AC)	Kusam LLP	90303100	11,475.00
	<b>PROFESSIONAL &amp; INDUSTRIAL GRADE DIGITAL CLAMP METERS</b>				
	<b>PROFESSIONAL GRADE DIGITAL CLAMP METERS</b>				
	KM 2780	3 <sup>3</sup> / <sub>4</sub> Digit 3,999 Counts 1000A AC Digital Clampmeter	Kusam LLP	90303390	3,350.00
	KM 2775	3 <sup>3</sup> / <sub>4</sub> Digits 4000 Counts, 2000A AC/DC Autoranging Digital Clampmeter	Kusam LLP	90303390	17,225.00
 	<b>INDUSTRIAL GRADE DIGITAL CLAMP METERS</b>				
	KM 2719	3 <sup>3</sup> / <sub>4</sub> Digits AC TRMS Digital Clampmeter	Kusam LLP	90303390	3,275.00
	KM 3060	3 <sup>1</sup> / <sub>2</sub> Digit 1,999 Counts 1000A AC Digital Clampmeter	Kusam LLP	90303390	3,275.00
	KM 3060-T	3-5/6 Digits 5,999 Counts 1000A AC Digital Clampmeter	Kusam LLP	90303390	3,275.00
	2790	3 <sup>3</sup> / <sub>4</sub> Digit 3999 Counts Liquid crystal LCD Display AC/DC Digital Clampmeter (1000A)	Kusam Ele/ Kusam LLP	90303390	3,275.00
	2781	3 <sup>3</sup> / <sub>4</sub> Digit 3999 Counts Liquid crystal LCD Display AC/DC Digital Clampmeter (1000A)	Kusam LLP	90303390	A price
	2700	3 <sup>1</sup> / <sub>2</sub> Digits 1999 Counts (300A) AC Clampmeter	Kusam Ele/ Kusam LLP	90303390	3,600.00
	KM999A+	4 Digit 6000 Counts 1000A Digital AC Clamp meter with Inrush Current	Kusam Ele	90303390	5,400.00
	KM9999A+	3-5/6 Digit 6000 Counts 1000A Digital AC/DC Clamp meter	Kusam Ele	90303390	7,575.00

	MODEL	DESCRIPTION	COMPANY REFERENCE	HSN CODE	UNIT PRICE	
 	<b>ANALOG INSULATION RESISTANCE TESTER</b>					
	KM 81	Analog insulation tester 1000v/2000 megohms; 600V AC	0-	Kusam LLP	90303390	2,925.00
	33-66KV	Highly Insulated FRP Earth / Discharge Rod 4 Sec Bu on type locking System, 10 sq.mm copper cable of 07 mtr. Long with cover		h Kusam LLP	39269099	8,100.00
	11-33KV	Highly Insulated FRP Earth / Discharge Rod 3 Sec Bu on type locking System, 6 sq.mm copper cable of 06 mtr with cover		h Kusam LLP	39269099	6,900.00
	11-KV	Highly Insulated FRP Earth / Discharge Rod 3 Sec Bu on type locking System, 4 sq.mm copper cable of 06 mtr with cover		h Kusam LLP	39269099	6,050.00
	<b>DIGITAL ELCB TESTERS</b>					
	KM 1812 EL-B	Digital ELCB Tester - 230Vac, Max, current 500mA		Kusam LLP	90318000	A price
	<b>DIGITAL TACHOMETER / STROBOSCOPE</b>					
	KM-2235B	Digital Tachometer (Contact Type) 5 - 999 / 19,999 RPM		Kusam Ele/LLP	90292010	3,960.00
		Accessories for KM 2235B : Set of Surface speed Test Wheel, RPM Adapter (cone) & (funne)		Kusam Ele/LLP	85069000	950.00
	KM-2234BL	Digital Tachometer (Non-Contact Type) 5-9999/99,999RPM		Kusam Ele/LLP	90292010	4,275.00
	KM-2241	Non Contact (Photo) Tachometer 2.5 - 99,999RPM & Contact Tachometer 0.5-19,999 RPM, Surface Speed 0.05-1,999.9M/Min		Kusam Ele/LLP	90292010	5,475.00
		Reflec for Tachometer (Non-Contact type) Model No. KM 2234BL & KM 2241 (12mm x 100mm) x 6 NOS		Kusam Ele/LLP	85069000	130.00
Adaptor for KM 2241			Kusam Ele/LLP	90299000	950.00	
 	<b>DIGITAL LUX METER</b>					
	KM-LUX-99	Range 0 - 2000 / 20000 / 100,000 LUX. Resolu on : 1Lux/10Lux/ 100Lux		Kusam Ele	90275090	2,600.00
	KM-LUX-200K	Range 0 - 200,000 LUX, 0.01-20,000 FC Resolution : 0.1Lux & 0.01FC		Kusam Ele/LLP	90275090	4,775.00
	IRL-380	Infrared Thermometer with Temperature range-50°C to 380°C & DS Ra 12:1 Emissivity : Adjustable (0.1 to 1.0)		Kusam Ele	90251990	1,500.00
	IRL-900	Non-Contact with laser sighting, Range: 30°C to 550°C, D:S Ra 0 10:1		Kusam Ele	90251190	7,650.00
	IRL-1100	Infrared Thermometer with Temperature range -50°C to 1100°C D:S RA 50:1		Kusam Ele	90251990	4,100.00
	IRL-1600	Infrared Thermometer with Temperature range -50°C to 1600°C D:S RA 50:1		Kusam Ele	90251990	8,300.00

**SANJAY**  
electrical

**House of Switchgear, Control Panel Accessories, Wires & Cables**

Pittale Apartment, First Floor, 527 Budhwar Peth, Tapkir Galli, Pune - 411002.  
 ☎ : 24456774, 24491816, 66029641 / 642.  
 M : 7875758405 / 08. 7875758265 / 7875758239  
 Email : sales@sanjayelectricalspune.com  
 ● accounts@sanjayelectricalspune.com  
 www.sanjayelectricalspune.com

**TERMS & CONDITIONS :**

- PRICES ARE SUBJECT TO CHANGE WITHOUT ANY PRIOR NOTICE.
- GST EXTRA AS APPLICABLE
- GOODS SOLD WILL NOT BE TAKEN BACK
- THIS PRICE LIST CANCELS ALL OUR PREVIOUS PRICE LISTS.
- SUBJECT TO PUNE JURISDICTION ONLY.