

# CRIMPING TOOLS - INSULATED TERMINAL

## JG-HSC8 6-4

- Self-adjusts to the desired ferrule size
- Ferrule insertion on the side of the tool
- Multiple crimp profiles
- Burnished or chrome finish
- Specially hardened spring steel

Specification	JG-HSC8 6-4
Crimping capacity	0.25-6.0mm <sup>2</sup>
AWG	23-10AWG
Length	175mm
Weight	0.36Kg



## JG-HSC8 6-6

Specification	JG-HSC8 6-6
Crimping capacity	0.25-6.0mm <sup>2</sup>
AWG	23-10AWG
Length	175mm
Weight	0.36Kg

- Ferrule insertion on the side of the tool
- Self-adjusting adaptation to the desired end sleeve (ferrule) size, no wrong crimps caused by using the wrong die
- Fits all ferrules within the application range
- Chrome vanadium electric steel in special quality, oil-hardened



## JG-HS-06WF

Specification	JG-HS-06WF
Crimping capacity	0.25-6.0mm <sup>2</sup>
AWG	24-10AWG
Length	203mm
Weight	0.4Kg



## JG-HS-16WF

Specification	JG-HS-16WF
Crimping capacity	6.0-16.0mm <sup>2</sup>
AWG	10-6AWG
Length	203mm
Weight	0.4Kg