

CRIMPING TOOLS - FOR CABLE LUGS

- The crimping tools is used for non-welding and standard electrical connection.
- The mould of the crimping dies is made of SCM-40 hardest tool steel. It is with the characteristics of long life, accurate bore diameter and good crimping effect.



Item No.	Range of Application	Crimping Capacity		Length(mm)	Weight(kg)
		mm ²	AWG		
JG-HX-50B	BS Standard type terminals	6-50	10-1	390	1.3kg
JG-HX-120B	BS Standard type terminals	10-120	8-4/0	620	4.0kg
JG-HX-150B	BS Standard type terminals	25-150	4-300MCM	620	4.0kg
JG-HX-245B	BS Standard type terminals	70-240	2/0	980	5.6kg



CRIMPING TOOLS - FOR CABLE LUGS

JG-YQK300

- It is applied to overhead distribution and press connection for copper terminals and sleeve of underground cable.
- Hexagonal mould is adopted to ensure tight press connection, good electric conduction and non-easy shedding.

Range of application	10-185mm ² (Al Terminal) 16-300mm ² (Cu Terminal)
Crimping force	8ton
Stroke	16mm
Standard	16,25,35,50,70,95,120,150,185,240,300mm ²
Weight	6.4Kg
Packaging Size	755x130x230mm
Package	Plastic case



JG-FYQ-400

Range of application	50-400mm ²
Crimping force	16ton
Stroke	20mm
Standard	50,70,95,120,150,185,240,300 400mm ²
Weight	9Kg
Packaging Size	355x90x155mm
Package	Steel case

