


NYLON CABLE GLANDS

PG THREAD CABLE GLANDS




Material : Nylon(PA)
 Sealing Element :NBR
 Protection level : IP68
 Ambient temperature : static-40°C-100°C, short 120°C
 dynamic -20°C-80°C, short 120°C
 Colour : White Grey Black

Code	Model Thread	Cable Range	GL (mm)	H (mm)	Spanner Size A & E (mm)
JG 7	PG 7	3 ~ 6.5	8	21	15
JG 9	PG 9	4 ~ 8	8	22	19
JG 11	PG 11	5 ~ 10	8	25	22
JG 13.5	PG 13.5	6 ~ 12	9	27	24
JG 16	PG 16	10 ~ 14	10	28	27
JG 18	PG 18	12 ~ 16	11	29	27
JG 21	PG 21	13 ~ 18	11	31	33
JG 25	PG 25	14 ~ 21	12	32	36
JG 27	PG 27	15 ~ 23	12	33	38
JG 29	PG 29	18 ~ 25	11	39	42
JG 36	PG 36	22 ~ 32	13	48	53
JG 42	PG 42	32 ~ 38	13	48	60
JG 48	PG 48	37 ~ 44	14	49	65
JG 63	PG 63	40 ~ 50	29	95	75

NYLON CABLE GLANDS

M THREAD CABLE GLANDS

Code	Model Thread	Cable Range	GL (mm)	H (mm)	Spanner Size A & E (mm)
JG - M12	M 12x1.5	3 ~ 6.5	8	21	15
JG - M16	M 16x1.5	4 ~ 8	8	22	19
JG - M20	M 20x1.5	6 ~ 12	9	27	24
JG - M25	M 25x1.5	12 ~ 16	11	29	27
JG - M32	M 32x1.5	15 ~ 23	12	33	38
JG - M40	M 40x1.5	22 ~ 32	18	45	46
JG - M50	M 50x1.5	32 ~ 38	18	47	56
JG - M63	M 63x1.5	37 ~ 44	20	47	68



Material : Nylon(PA)
 Sealing Element :NBR
 Protection level : IP68
 Ambient temperature : static-40°C-100°C, short 120°C
 dynamic -20°C-80°C, short 120°C
 Colour : White Grey Black

MG THREAD CABLE GLANDS

Code	Model Thread	Cable Range	GL (mm)	Spanner Size A & E (mm)
JG - MG20	MG 20x1.5	14 ~ 8.5	15	27/27
JG - MG25	MG 25x1.5	18 ~ 12.5	15	33/33
JG - MG32	MG 32x1.5	25 ~ 18	15	41/41
JG - MG40	MG 40x1.5	32.5 ~ 24	15	50/50
JG - MG50	MG 50x1.5	41 ~ 30	20	62/62
JG - MG63	MG 63x1.5	54 ~ 40	20	75/75



Thread Specification : Metric Teeth
 Material : Nylon PA66 (fire rating UL94V-2)
 Sealing Element :NBR
 Protection level : IP68
 Ambient temperature : static-40°C-100°C, short 120°C
 dynamic -20°C-80°C, short 120°C
 Colour : White Grey Black

